



## SPECIFIKACE VÝZTUŽE

PRIMER	CISLO	P	DELTA		CELLEN	OCELL
			mm <sup>2</sup>	kg		
CELEUM	1	R12	7-48	36	209,3	R12
	2	R12	3-61	8	26,9	
	3	R12	4,19	3,6	150,6	
	4	R12	3-44	3,8	130,7	
	5	R12	3-35	3,8	116,7	
	6	R12	3-35	4,0	113,7	
	7	R12	3-35	4,0	151,6	
	8	R12	3-35	3,9	147,8	
	9	R12	1-76	1,2	21,4	
	10	R12	1-19	5,4	64,3	
	11	R12	1-10	18,8	199,3	
	12	R12	1-34	15	20,1	
	13	R12	1-34	15	20,1	
	14	R12	3-105	58	174,0	
	15	R12	3-35	5,8	47,3	
	16	R12	3-4-00	1	64,0	
	17	R12	1-1,77	9,4	109,5	
	18	R12	3-35	1,5	52,6	
	19	R12	3-35	15	50,5	
	20	R12	3-35	3,6	69,3	
21	R12	1-53	15,0	2209,2		
mm <sup>2</sup>						
kg/m <sup>3</sup>	1961				1961	

NAVŘŽENO DLE ČSN EN 1992 - 1 - 1 (EUROKÓD 2).

[illegible]

INVESTOR/CUSTOMER	Autoinvest, LLC
MADE IN	Ing. Zvonik OOO
ADDRESS	Ing. Zvonik OOO
DATE	June 22, 2008
2008	June 22, 2008

TĚŽKÁ KONSTRUKCE SA (NAVRHOVÁ ŽIVOTNOST 80 LET) DLE ČSN EN 1990  
POŽÁRNÍ ODOLNOST R1 60  
BEŽNÍ C 2025 - XC1 (C2) - C1-0,2 - Dmax 16 - SA - DLE ČSN EN 206-1 ZMĚNÁ Z  
VÝZTUŽ B 500B (10 505 9 (R))  
KRYTÍ 25 mm

